

NO	TEN MENTEN					_ I\
NO.	ITEM	MAT'L	SIZE	FORD	MUELLER	McDONALD
1	METER SETTER	COPPER	1"	FORD VBH94-15W-MM-44ZA-NL WITH VERITCAL INLET MUELLER 391B24104R2-80N AY MCDONALD 762P415WCPP44X15		
2	CORPORATION STOP	FOR COPPER SERVICE	1"	FB-1000-4-Q	B25008N	74701BQ
3	PIPE	COPPER	1"	FEDERAL SPEC. WW-T-799, TYPE K ASTM SPEC. B88, TYPE K A.W.W.A. SPEC. 7S-CR, TYPE K		
4	METER (FURNISHED BY AWWD)					
5	METER BOX		1"	REFER TO DETAIL WD-2 FOR METER BOX TYPE		
6	PVC CAP AT END OF TAIL PIECE					
7	ADAPTOR		1"	F.I.P.T x COMPRESSION	JOINT MATCHING S	SETTER MANUFACT.
8	4" DI SADDLE		1"	FORD - FSD202 4.74-5.26 O.D. (C.C.	ROMAC – THREAD) 4.5 –5.4	202NS
9	SST 1-1/4" ROUND TAG W/ ADDRESS OR LOT NUMBER FOR CLUSTERED BOXES					

NOTES:

A. SPLICES — NOT ALLOWED UNLESS APPROVED BY THE DISTRICT. USE MUELLER 110 OR FORD COMPRESSION JOINT.


B. OWNERS ARE RESPONSIBLE FOR INSTALLING PRESSURE REDUCER ON THEIR SYSTEM TO PROTECT THEIR FACILITIES FROM HIGH PRESSURE, EXCEPT AS OTHERWISE DIRECTED BY DISTRICT.

C. SURFACE RESTORATION IN ACCORDANCE WITH JURISDICTIONAL AUTHORITY.

D. 4" OF SAND BEDDING REQUIRED ON ALL COPPER SERVICE LINES.

E. WHEN SIDEWALK IS INSTALLED BEHIND METER BOX, A COPPER TAILPIECE OF LIKE LENGTH SHALL BE EXTENDED TO THE PROPERTY SIDE OF WALKWAY.

F. ALL FITTINGS SHALL BE "LEAD FREE"



1" SERVICE INSTALLATION

DATE: 7 JAN 2020

DWG. WD-4

APPROVED BY: _

ENGINEERING & DEVELOPMENT DIRECTOR